



PORTABLE VMD (Trailer Mounted)

✉ sales@sensecure.in | service@sensecure.in | support@sensecure.in

🌐 www.sensecure.in 📞 1800-889-4139

PORTABLE VMD

(Trailer Mounted)

Parameters	VMS Type-(Full Matrix)
Display Size (W x H)	Size 1: 640*640 Size 2: 960*960
LED Configuration	RGB 3 in 1 SMD
Pixel Pitch	P8 or Lower (Better)
Brightness (Calibrated)	5000 cd/m ² or better
Grey Scale Processing	12 Bit or better
Pixel Density Half Gain Horizontal / Vertical Viewing Angle	Minimum 27777 pixels per sqm or higher Minimum H 140 deg / V 130 deg ±10 degree or better
Refresh Rate	≥3840 Hz or better
Contrast Ratio	4000:1 or better
Processor	
Controller/Processor	Should be same make/OEM
Internal drive	Minimum 32 GB
Audio	MP3, WAV or equivalent
Image	JPEG, PNG, BMP, GIF, PDF etc
Text	Multiple fonts, Speeds, colours, animations
Network	Ethernet 1000/100/10 (RJ45) and GPRS
URL Video / Audio /Website	Direct playback of URLs
Viewing distance	>100 meters
Display capability	Alpha-numeric, Pictorials, Graptical & video
Language	Bilingual (English/Hindi) and all fonts supported by windows
Auto Dimming In built Sensor	Auto dimming adjusts to ambient light level. (Photoelectric sensor)
Brightness & contrast	Controlled through software