



TRAFFIC BLINKER

✉ sales@sensecure.in | service@sensecure.in | support@sensecure.in

🌐 www.sensecure.in 📞 1800-889-4139

ROAD SAFETY

TRAFFIC BLINKER

S/N	SPECIFICATION	DETAILS
1	Blinker Size	300mm (12 Inch) & 200 mm (8 Inch)
2	Body	Molded Polycarbonate, Suitable for Extreme weather conditions
3	Lens	U.V.Stabilized, Transparent Polycarbonate
4	Gasket	Rubber Gasket For Sealing Between Lens & Signal Unit
5	Color	Red/Amber/Green
6	PCB Used	1.5 mm Thick, Glass Epoxy for Power Supply/ LED Display
7	LED Used	Ultra Bright, Water Clear
8	Viewing Angle	24 Degree for Led's
9	No. Of LED's	170 LED (300 mm), 90 LED (200 mm)
10	Charge Control Unit (CCU)	Built in Type, Help to protect Battery from Deep Discharging as well as overcharging, also protect panel from Reverse voltage.
11	Solar Panel	12 Volt, 20 Watt. Or As per requirements
12	Battery	(SMF) Sealed maintenance Free Type (Brand: Exide- 12volt, 7AH)
13	Working Voltage	12v DC
14	Frequently	30 to 40 Flasher Per Minute as desired
15	Power Factor	>0.9
16	Visibility	600 Mts. Good Even During Bad Weather
17	Certification	IP65

Note: Pictures shown above are symbolic; Actual Product may vary as per future developments & requirements by shown images and parameters.